

exterior low lustre 201 LINE

American Pride® paints are high performance exterior coatings which are low in odor during application and drying. These products are ideal for use in occupied areas because of their low odor and zero VOCs (Volatile Organic Compounds).

RECOMMENDED USE

American Pride® Exterior Low Lustre is a premium quality paint that provides durable color and protection for a variety of exterior surfaces. This product is ideal for previously painted or primed surfaces such as vinyl, aluminum siding, wood siding, masonry, shutters, fencing and hardboard.

SURFACE PREPARATION

See Surface Preparation Section on Paint Label.

Wood:

American Pride® Multi-purpose Primer should be used to seal any unprimed drywall or patching.

Vinyl or Aluminum siding:

Darker colors than the original siding should not be used due to the possibility of warping. Prime with American Pride® Multi-purpose Primer

Masonry:

Allow new stucco, plaster, and masonry to cure 30 days before priming with American Pride® Multi-purpose primer.

Metal:

Prime with an appropriate primer before applying this product.

EQUIPMENT

Conv. Spray :	40 PSI TIP: 704/FX
Airless Spray :	1800 - 2400 PSI TIP: .015" - .021"
Brush :	Polyester or Nylon
Roller :	3/8"-1/2" Nap Cover
Pad :	Standard

*VOC level as determined on untinted paint within the precision of ASTM D3960

GREEN WISE CERTIFICATION

American Pride® Paint products that display the GREEN WISE mark are tested and certified by Coatings Research Group, Incorporated. These products meet or exceed environmentally determined testing standards and are environmentally preferred over traditional paints and coatings. Visit www.greenwisepaint.com to view product standards.

THINNER & CLEAN-UP

Thinning is not recommended, but if necessary, use clean water sparingly. Soap and water clean-up.

LIMITATIONS

- Do not apply when air, surface, or product temperature is below 50°F (10°C) or if temperature might drop to this level within 4 hours of application.
- Do not apply in temperatures above 85°F (29°C).

PACKAGING

Quarts, Gallons, 5 Gallons

COLORS

- 1232 palette colors
- Computer color matching available

SPECIFICATION DATA **

Type :	100% Acrylic Latex
Finish :	Satin
» Sheen: at 85°	14 to 19 (Substrate Dependent)
% Solids (varies with color) :	
» By Weight:	59 ±2%
» By Volume:	41 ±2%
Wt./gallon (white only) :	11.83 lbs/gal
Flashpoint :	212°F (PMCC)
VOC lbs./gal. (max) :	0*
VOC grm./ltr. (max) :	0*
Thinner :	Water
Clean-up :	Soap and Water
Dry Time :	
» To Touch:	2 hours
» To Recoat:	4-8 hours
» To Service:	Overnight
Note: Adding large amounts of zero VOC colorant can dramatically slow dry/cure time.	
Thickness :	
» Dry:	1.5 mil
» Wet:	4.0 mil
Coverage :	400 sq.ft./gal. (on smooth surfaces)
Flame Spread Rate :	Class A (0-25 on non-combustible surfaces)

**Product Data is based on AP 201-W